DERWENT-ACC-NO: 1990-083392

DERWENT-WEEK: 199011

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Landing mat with removable section - has recess on

upper surface

without core layer, fillable by section for conventional mat

or removable for

goal area

INVENTOR: SUNDOVIST, L E

PATENT-ASSIGNEE: SUNDQVIST L E[SUNDI]

PRIORITY-DATA: 1988SE-0002799 (August 3, 1988)

PATENT-FAMILY:

PUB-NO PUB-DATE LANGUAGE PAGES MAIN-IPC WO 9001355 A February 22, 1990 011 N/AAU 8940385 A March 5, 1990 N/A000 N/ASE 461766 B March 26, 1990 N/A

N/A

SE 8802799 A February 4, 1990 N/A

000 N/A

DESIGNATED-STATES: AT AU BB BR CH DE DK FI GB HU JP KP KR LK LU MC MG MW NL NO R O SD SE US AT BE CH DE FR GB IT LU NL OA SE

CITED-DOCUMENTS: SE 3939288; US 2207095 ; US 2462579

APPLICATION-DATA:

PUB-NO APPL-DESCRIPTOR APPL-NO

APPL-DATE

WO 9001355A N/A 1989WO-SE00425

August 2, 1989

INT-CL (IPC): A63B005/18; A63B006/00

ABSTRACTED-PUB-NO: WO 9001355A

BASIC-ABSTRACT: A multi-purpose mat for sporting use

comprises a central reinforcing core layer (2) of tough non-penetrable elastic material, two layers (1, 3) of sort shock absorbing resilient material e.g. foam rubber disposed on either face of the central layer and an outer protective covering (4, 4a) which adds strength to the mat.

Over part of the upper surface there is a recess (5) in which the core layer is absent. This may be filled by a closely fitting removable section (6) which comprises a layer (7) similar to the core layer a lower protective layer (13a) and upper protective layer (8). The removable section is fitted to fill the recess (5) giving conventional landing mat, or removed and the mat positioned vertically to form a goal area.

ADVANTAGE - Landing mat may be used as goal area instead of non useful storting.

CHOSEN-DRAWING: Dwg.2/4

TITLE-TERMS:

LANDING MAT REMOVE SECTION RECESS UPPER SURFACE CORE LAYER FILL SECTION
CONVENTION MAT REMOVE GOAL AREA

DERWENT-CLASS: P36

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1990-064255

PCT

(30) Priority data:

8802799-0

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:

A63B 5/18

(11) International Publication Number: WO 90/01355

(43) International Publication Date: 22 February 1990 (22.02.90)

SE

(21) International Application Number: PCT/SE89/00425

(22) International Filing Date: 2 August 1989 (02.08.89)

3 August 1988 (03.08.88)

(71)(72) Applicant and Inventor: SUNDQVIST, Leif, Erik [SE/SE]; Pl 8570, S-430 41 Kullavik (SE).

(74) Agent: AWAPATENT AB; Box 53252, S-400 71 Göteborg (SE).


(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent)

MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report. In English translation (filed in Swedish).

(54) Title: MULTIPURPOSE MAT FOR SPORTING



(57) Abstract

The object of the invention is to provide a multipurpose mat for sporting which can be used also for other exercises than the conventional mats, serving for example as landing beds for jumping. The mat according to the invention has in one flat side a recess (5) which extends through but a part of the thickness of the mat, the shape of said protective cover (4) of the mat conforming to the shape of the recess, and a filling piece (6) which corresponds to the shape of the recess, whereby the mat, in lay-flat condition and with its filling piece in position, can serve as a conventional landing bed, and, after removal of said filling piece and in upright condition can serve as a shock-absorbing goal marker for various types of ball games and the like.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
ΑU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark	MC	Monaco	US	United States of America
FI	Finland	MG	Modagacar	US	Office States of America

10

15

20

25

30

1

MULTIPURPOSE MAT FOR SPORTING

The present invention relates to a multipurpose mat for sporting, preferably of the type that is used as a landing bed for jumping.

When not in use, such landing mats are mostly kept standing on edge along one of the walls of the gymnasium, or they are in some way suspended. When standing or suspended, the mats are generally not used to any greater extent, which means that they are not put to use during most of the time that the gymnasium is open.

One of the objects of the present invention is to extend the field of application for such mats, so that the investment made when the mat is bought pays off as much as possible, at the same time as the purchase of some supplementary apparatus can be avoided.

The mat according to the invention is, in the main, characterised in that the mat which in per se known manner comprises a soft, shock-absorbing core surrounded by a flexible protective cover, is formed in one flat side with a recess which extends through but a part of the thickness of the mat and to the shape of which said protective cover conforms, and has a filling piece which corresponds to the shape of the recess and is preferably made of the same core material as the remainder of the mat, said filling piece having likewise a flexible protective cover, whereby the mat, in lay-flat condition and with its filling piece in position and preferably facing the floor, can serve as a conventional landing bed, and, after removal of said filling piece and in upright condition, can serve as a shock-absorbing goal marker for various types of ball games and the like.

The mat according to the invention may thus serve not only as a conventional landing bed, but for instance also as an efficient goal marker, which means that no

Here

Here

Action

Mere

Acti Here follows a description or an embodiment of the invention, which the device according to drawing in which the device according to device according to device according to device according to the device according to th special goal appliances need be acquired. WO 90/01355 the mat accompany and acamings in which: the mat showing is a perspective view showing is a perspective range. had to the accompanying drawings in which: rig. is a perspective view of its sides;

to the invention rice of the continuous according to the continuous rice of the continuous rice raing to the inventional view of the same mat from Fig. 2 is a sectional near here has been allowed as the filling of the fill rig. the floor his woult not have all rig. which the filling piece has been lifted up, on the floor by a vaulting norse, and the filling of the mat from which the filling of the mat from which is a reasonable of the filling of the filling of the filling of the mat from which is a reasonable of the filling of the mat from which is a reasonable of the mat from lying on the floor by a vaulting horse, Fig. 4 is a view of the mar from which is standing on edge

Fig. 4 is a view of the mar from which is standing on edge

Piece has been removed and which is arker

Piece has are for instance a mai marker as I for instance a your the mat according relative.

As is best seen from pig. 1-3 of a relative. As 15 pest seen from F19. 2, the mat according

As 15 pest seen from material each as form ruther

to the invention material each according

to the chock-absorbing material each according to the chock-according to the chock-accor precense as to serve as the for the form of the form o to the invention comprises a core 1-3 of a relatively to the core 1-3 of a relative to the core 1-3 of a relative to soft, shock-absorbing material, such as foam rubber.

soft, shock-absorbing material, such as foam rubber.

The core is provided with a flexible and durable pr The core is provided with a flexible and durable pro
tective reces & adanted to growmondate a filling of the core

tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate and durable pro
tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core tective reces & adanted to growmondate a filling of the core and the core tective reces & adanted to growmondate a filling of the core and tective cover 4. One side of the core and commodate a filling piece 6 accommodate a commodate a commod 10 With a recess hape as the recess and comprising having having naving the same snape as the recess and comprising, naving the remainder of the mat, and livewise moved the like like the remainder of the mat and likewise provided of the mat and likewise provided near of the mat and likewise provided and likew material as the rest of the mat and likewise provided the mat and likewise provided the mat and likewise provided with a flexible and durable protective of the mat which with a protective cover A on the rest of the mat which with a flexible and durable protective cover 8 similar which a flexible and durable protective reference numeral of the protective cover 4 on the rest of the numeral of the protective representation 15 to the protective cover 4 on the rest of the nat which to the protective is designated by reference numeral and into the in its entirety cover 4 has been noticed as a has near noticed in its entire cover 4 has near noticed as a has near notic in its entirety is designated by reference numeral 9.

In its entirety cover frilaw the walle of each reneed the pulled down into the walle of each reneed the walle of each reneed the walle of each reneed to cheen the walle of the wall of the walle of the walle of the walle of the walle of the wall of the walle of the walle of the walle of the walle of the wall of the wall of the wall of the walle of the walle of the walle o The protective cover follow the walls of said recess the walls of manner the arawing trecess to closely the arawing trees to closely the arawing trees to closely the arawing trees. recess 5 to closely tollow the walls of sala recess the drawings. The main part of the as can be seen in the seen as can be seen in the drawings. In this manner, of the main part 9 of recess 5 15 clearly visible in the main part y or t the mat. In the embodiment lilustrated, the recess mat, 10 of the mat, 10 of the edge the edge the edge and the edge the 5 15 open at one longitudinal side edge the side and in of and velcro fasteners away from the side and renees furthest away from the side and renees furthest away from the side and velcro fasteners. and velcro fasteners 11 are provided on the side edge 10 of the side furthest away from the side of the recess furthest away from fasteners 12 connerstite of the recess furthest away from fasteners 12 connerstite the mat or the recess furthest away trom the side edge 10 of the recess furthest away trom fasteners 12 cooperating the mat, relative fasteners 11 heing provided on the the mat, relative fasteners 25 the mati corresponding velcro rasceners 12 cooperation the with the velcro fasteners 11 being provided on the with the velcro fasteners 12 cooperation of the with the velcro fasteners 12 cooperation to the velcro With the velcro tasteners in being provided on the core that the filling piece 6. The core the filling piece 6. The core the filling piece 6. The core the frament of the f corresponding edge of the frequently comprises two soft nats frequently comprises two layer

elastic layers 1, 3 disposed each on one side of a tough reinforcing layer 2 which is stronger than the two layers 1 and 3. The reinforcing layer 2 mainly serves to prevent penetration. In the embodiment shown, where the core comprises said three layers, the recess 5 extends down to the reinforcing layer 2. When the mat is used as a landing bed, as is shown in Fig. 3, the reinforcing layer of this embodiment is thus supplemented with the inner part 13a of the protective cover 13 of the filling piece 6, and with the part 4a of 10 protective cover 4 on the main part 9 of the mat that is situated inside the recess 5. Thus, it is possible to further strengthen the reinforcing layer. When the filling piece 6 is relatively large and thus extends across the whole landing area, the ordinary reinforcing 15 layer 2 may in some cases be left out, since the protective cover per se serves as a reinforcement. When a mat provided with a filling piece is used as a landing bed, the filling piece should be facing downwards, 20 in order to avoid that someone lands in the gap area between the filling piece 6 and the main part 9 of the mat. Since the boundary between the filling piece 6 and the remainder of the mat will be situated inside the mat, and because of its penetration-preventing function, the core part of the rest of the mat can be produced in a less costly way than is otherwise the case. This natural reinforcement is obtained because the recess 5 into which the filling piece 6 fits, extends through but a part of the thickness of the mat. Naturally, it is possible to arrange other fastenings 30 than the velcro fasteners 11, 12, and the fastenings can be disposed elsewhere in the surface layer between the main part 9 of the mat and the filling piece 6, than is shown in the drawings.

When the mat is placed in upright condition, as shown in Fig. 4, and the filling piece has been removed, the recess in the mat can serve as an efficient

PCT/SE89/00425

5

10

15

4

goal marker for ball games and the like. Thus, the mat serves as an efficient shock-absorber, a great advantage at ball games because incoming balls stay within the goal area and do not bounce back into the field. In the embodiment shown, where the recess is open at one of the side edges of the mat, it is suitable to use the mat as a goal marker for such ball games as for instance handball, but using the mat for other ball games is, of course, within the scope of the invention. Furthermore, the recess may be located elsewhere in the mat, or have another shape.


The present invention is not limited to the abovementioned embodiment shown in the drawings and chosen by way of example, but can be varied in its details within the scope of the appended claims without departing from the spirit of the invention.


5


CLAIMS

- 1. Multipurpose mat for sporting, suitably of the type that is used as a landing bed for jumping, characterised in that the mat which in per se known manner comprises a soft shock-absorbing core (1-3) surrounded by a flexible protective 5 cover (4), is formed in one flat side with a recess (5) which extends through but a part of the thickness of the mat and to the shape of which said protective cover (4) conforms, and has a filling piece (6) which corresponds to the shape of the recess and is pre-10 ferably made of the same core material as the remainder of the mat, said filling piece having likewise a flexible protective cover (13), whereby the mat, in lay-flat condition and with its filling piece (6) in position 15 and preferably facing the floor, can serve as a conventional landing bed, and, after removal of said filling piece and in upright condition, can serve as a shock-absorbing goal marker for various types of ball games and the like.
- 20 2. Multipurpose mat as claimed in claim 1, the core of which is divided by a reinforcing layer (2) extending along the plane thereof, c h a r a c t e r i s e d in that the recess (5) is located on one side only of the reinforcing layer.
- 25 3. Multipurpose mat as claimed in claim 1 or 2, c h a r a c t e r i s e d in that the recess (5) is open at one side edge (10) of the mat.
 - 4. Multipurpose mat as claimed in any one of the preceding claims, c h a r a c t e r i s e d in that the filling piece (6) and the recess (5) on their opposing surfaces have mutually cooperating fastening members (11, 12), such as velcro fasteners.
 - 5. Multipurpose mat as claimed in claim 4, c h a r a c t e r i s e d in that the fastening members

are disposed at the edge of the recess (5) which is situated furthest away from the edge (10) of the mat where the recess is open.







INTERNATIONAL SEARCH REPORT

International Application No PCT/SE89/00425

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)									
According to international Patent Classification (IPC) or to both National Classification and IPC 4									
	3 B 5/18								
II. FIELD	S SEARCH		nentation Searched ?						
Classificat	on System	Finning or we write	Classification Symbols						
IPC	4	A 63 B 5/00, /16, /18,							
US		<u>272</u> : 93, 101, 109; <u>5</u> :							
Documentation Searched other than Minimum Documentation to the Extent that such Documente are included in the Fields Searched •									
SE, NO, DK, FI classes as above									
III. DOCL	MENTS CO	NSIDERED TO BE RELEVANT							
Category *		n of Document, 31 with Indication, where as	ppropriate, of the relevant passages 12	Relevant to Claim No. 13					
A	SE, B	, 393 928 (HARGEST, T. 31 May 1977	S)	,					
А	US, A	S, A, 2 207 095 (HUTCHINSON, F.M) 9 July 1940							
А	US, A	US, A, 2 462 579 (WARNER, L.W) 22 February 1949							
"A" doct cons "E" earli filing "L" doct which citat "O" doct othe "P" docu later	iment defining idered to be of er document to grades iment which is h is cited to ion or other a ir means iment publishe	cited documents: 19 the general state of the art which is not of particular relevance out published on or after the international may throw doubts on priority claim(s) or setablish the publication date of another pecial reason (as specified) to an oral disclosurs, use, exhibition or not prior to the international filing date but rity date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "4" document member of the same patent family						
Date of the	Actual Comp	letion of the International Search	Date of Mailing of this International S	earch Report					
	1989-0	09-26	198 9 -10- 0 6						
Internations	Searching A	uthority	Signature of Authorized Officer	/					
	Swedis	sh patent Office	Christer Bäcknert						

Form PCT/ISA/210 (second sheet) (Jenuary 1965)